Diaphragm Water Pumps







- High solids handling
- Petrol or diesel options
- 'Snore' allows machine to run dry with no damage to the pump end
- Easy wheel chassis

Diaphragm Pumps

2" & 3" diaphragm pumps ideal for indefinite dry running with no damage to the pump.

SIZE	2"	2"
MODEL	Sprite	Deluxe
HILTA REF	H000155	H000154Y
FRAME/CHASSIS TYPE	Easy Wheel	Wheelbarrow
POWER	Petrol	Diesel
ENGINE TYPE	Honda GX120 3.2bhp 2.4kW 3000rpm	Yanmar LN48 2.3bhp 1.7kW 1850rpm
AVERAGE SOUND PRESSURE LEVEL @ 7m	77dB(A)	76dB(A)
MAX OUTPUT	11.36m³/hr 2500gal/hr	
MAX DRY SUCTION LIFT	6 metres	
TOTAL HEAD	18 metres	
MAX SOLIDS	20mm	
STARTING	Recoil	Electric/Recoil
FUEL TANK CAPACITY (LITRES)	2.5ltr	5.5ltr
DIMENSIONS (LxWxH)mm	740 x 450 x 570	1230 x 530 x 710
WET WEIGHT	45kg	111kg



i catules:

- High solids handling
- 'Snore' allows machine to run dry with no damage to the pump end
- Two wheel site chassis
- Also available with 24 hour long running fuel tank

SIZE	3"	3"
MODEL	Drysite D5	
HILTA REF	H000090YE	H000090YE-24HR
FRAME/CHASSIS TYPE	Two Wheel Site Chassis	
POWER	Diesel	
ENGINE TYPE	Yanmar LN48 2.7bhp 2.0kW 2000rpm	
AVERAGE SOUND PRESSURE LEVEL @ 7m	76dB(A)	
MAX OUTPUT	22.73m³/hr 5000gal/hr	
MAX DRY SUCTION LIFT	7 metres	
TOTAL HEAD	20 metres	
MAX SOLIDS	40mm	
STARTING	Electric/Recoil	
FUEL TANK CAPACITY (LITRES)	5.5ltr	21ltr
DIMENSIONS (LxWxH)mm	1525 x 620 x 840	1650 x 620 x 920
WET WEIGHT	150kg	177kg



All hoses and fittings available for all pumps Specifications are subject to change without prior notice

Applications















