

LAWNNAIRE® V PLUS AERATOR



The **First Name** in Turf Renovation™

Built tough for the utmost in productivity and featuring a ground speed of up to 40,000 square feet per hour, the Lawnnaire® V Plus Aerator has been designed with added reliability and operator comfort. This unit provides extra stability on slopes to keep you moving.

Removable rear wheels will help you get through narrower gates and give you the flexibility to aerate backyards with ease.

**Removable Weights
and Fillable Water
Drum**



**HIGH PRODUCTIVITY
(UP TO 40,000 SQ. FT./HR.)**

TOUGH SOIL CONDITIONS



LAWNIRE® V PLUS AERATOR



The **First Name** in Turf Renovation™

Easy-to-Use Separate Throttle

Handle-mounted design allows you to select any speed you desire



Tight Areas

The removable rear wheels allow you to get through tight areas such as gates



Tough Soil Conditions

Removable weights and fillable water drum add weight for greater tine penetration



HELPFUL HINT: Do not leave drum filled with water for extended periods of time or in cold weather.

HONDA® #744910B	SPECIFICATIONS	BRIGGS & STRATTON® #744911C
GX120 4-cycle	ENGINE	Intek™ 900 4-cycle
0.56 L (0.59 U.S. qt., 0.49 Imp. qt.); 10W-30	ENGINE OIL CAPACITY AND TYPE	0.59 L (0.63 U.S. qt., 0.52 Imp. qt.); 10W-30
Belt tightener	CLUTCH	Belt tightener
Primary – 4L-section V-belt Tine and Drum – Single #40 nickel-plated chain	DRIVE	Primary – 4L-section V-belt Tine and Drum – Single #40 nickel-plated chain
(42) 0.75 in. (19 mm) diameter coring type formed from 0.08 in. (2 mm) hollow, austempered alloy steel	TINES	(42) 0.75 in. (19 mm) diameter coring type formed from 0.08 in. (2 mm) hollow, austempered alloy steel
26.5 in. (673 mm)	AERATING WIDTH	26.5 in. (673 mm)
Up to 2.75 in. (70 mm)	CORING DEPTH	Up to 2.75 in. (70 mm)
0.75 in. (19 mm)	CORING DIAMETER	0.75 in. (19 mm)
3.75 in. (95 mm) x 7 in. (178 mm)	AERATION PATTERN	3.75 in. (95 mm) x 7 in. (178 mm)
Up to 9/sq. ft. (0.8 m ² /hr.)	HOLES PER SQ. FOOT (SINGLE PASS)	Up to 9/sq. ft. (0.8 m ² /hr.)
Aerates up to 40,400 sq. ft./hr.	PRODUCTIVITY (EST.)	Aerates up to 40,400 sq. ft./hr.
(2) 8 x 2.5 semipneumatic with ball bearings	TIRES	(2) 8 x 2.5 semipneumatic with ball bearings
Dry – 228 lbs. (103 kg) Dry with Weights – 280 lbs. (127 kg) Water in Drum with Weights – 330 lbs. (150 kg)	WEIGHT	Dry – 228 lbs. (103 kg) Dry with Weights – 280 lbs. (127 kg) Water in Drum with Weights – 330 lbs. (150 kg)
Width – 36 in. (914 mm) Length – 53 in. (1346 mm); 46 in. (1168 mm folded) Height – 48 in. (1219 mm); 28 in. (711 mm folded)	DIMENSIONS	Width – 36 in. (914 mm) Length – 53 in. (1346 mm); 46 in. (1168 mm folded) Height – 48 in. (1219 mm); 28 in. (711 mm folded)
2 year commercial (engines warranted separately from manufacturer)	WARRANTY	2 year commercial (engines warranted separately from manufacturer)



P.O. Box 469, Johnson Creek, WI 53038-0469
©2010 Schiller Grounds Care, Inc. All rights reserved.

Specifications subject to change without notice. See our full line brochure for complete specifications and options.

